High Purity (Al₂O₃) Alumina 99.8% Material Specifications

Alumina Oxide (Al_2O_3) is a readily available material with reasonable processing cost, possessing excellent mechanical, electrical, and wear properties. Our fabricated Alumina is used in a wide range of applications not limited to aerospace, automotive, medical and military.

Technical Products processes include cold isostatic pressing of green billets, pre-fired machining, sintering, and post sintered grinding operations.

Physical Properties	Units	Al ₂ O ₃ -99.8%
Bulk Density	g/cm³	3.9
Color	-	ivory
Water Absorption	%	0
Hardness (Rockwell 45 N)	-	83
Grain Size	Microns	6

Mechanical Properties	Units	Al ₂ O ₃ -99.8%
Compressive Strength	MPa	2300
Modulus of Elasticity	GPa / psi • 10 ⁶	370 / 54
Flexural Strength	MPa /psi • 10 ³	375 / 54
Poisson's Ratio	-	0.22
Fracture Toughness	MPa m ^{1/2}	4 - 5
Gas Permeation	%	0

Thermal Properties	Units	Al ₂ O ₃ -99.8%
Max. Use Temperature (no load)	ºC / ºF	1700 / 3092
Thermal Conductivity	W/mK	30
Thermal Expansion 20°C – 1000°C	10 ⁻⁶ /ºC	8.2
Specific Heat	J/kg*K	880

Electrical Properties	Units	Al ₂ O ₃ -99.8%
Dielectric Constant	-	9.8
Dielectric Strength	ac V/mils	220

^{**}The information provided in this table is a compilation of publicly available data. This information is provided for comparison purposes only, and is not intended to be warrantable. Further, *Technical Products, Inc.* disclaims any and all liability from errors, in accuracies, or omissions.